

UNITE® 20 Pro Webcam




Pro Webcam with 85° ultra wide-angle field-of-view for use on your PC or laptop display to provide a full 1080p30 image.



Enjoy superior desktop camera quality

Easily mounts on your PC or laptop display to provide a full 1080p30 image with an ultra wide-angle field-of-view.

- > Supports up to 1080p@30 Full HD.
- > 85° ultra wide-angle field-of-view.
- > Full-featured USB 2.0 interface, power supply, 2-channel USB video
- > Super-high SNR with advanced 2D and 3D noise reduction
- > Easily mounted on PC or laptop display
- > Use with PC or laptop and web conferencing applications such as Microsoft® Teams, Zoom™, WebEx™, GoToMeeting™, and others.
- > Pair the new UNITE 20 Pro Webcam with a ClearOne CHAT 50 or CHAT 150 speakerphone for the ultimate personal collaboration workspace for both highquality video and audio.



Unmatched for desktop collaboration

Use with PC or laptop and webconferencing applications such as Microsoft® Teams, Zoom™, WebEx™, GoToMeeting™, and others.

Great Ideas Need to be Seen®

APPLICATIONS

- BYOM Video Conferencing
- BYOM Audio Conferencing
- In-Room Presentation

WORKSPACES

- Small to mid-sized meeting rooms
- Boardrooms
- Executive Offices
- Classrooms

UNITE® 20 Pro Webcam

VIDEO SYSTEM

- VIDEO INPUTS**
 - 1080P Full HD
 - Sensor: 1/2.7", CMOS, Effective Pixel: 2.07 M
 - Scanning Mode: Progressive
 - Lens: Focus: f=2.8 mm, FOV: 85°
 - Minimal Illumination: 0.05 Lux @ (F1.8, AGC ON)
 - Shutter: 1/30s – 1/10000s
 - White Balance: Auto, Indoor, Outdoor, One Push, Manual
 - Backlight Compensation: Supported
 - Digital Noise Reduction: 2D & 3D Digital Noise Reduction
 - Horizontal Angle of View: Wide angle up to 85°
 - Easy Installation: Equipped with damped rotary shaft bracket to fit almost any display, easy to install, stable and reliable.
- AUDIO**
 - Built-in microphone array
- USB FEATURES**
 - Operating Systems
Windows® 7 (1080p and under only), Windows 8.1, Windows 10 or higher, Linux macOS™ 10.10 or higher, Google™ Chromebook™ Version 29.0.1547.70 or higher, 2.4 GHz Intel® Core 2 Duo processor or higher, 2 GB RAM or more, USB 2.0 port
 - Color System / Compression: H.265 / H.264 / MJPEG
 - Video Format: 1080p@30fps/25fps, 720p30/25, 960 x 540p30/25, 640 x 360p30/25
 - USB Video Communication Protocol: UVC 1.0 ~ UVC 1.5 (Optional)
- INPUT/OUTPUT INTERFACE**
 - USB Interface: 1 x USB 2.0: Type A
- GENERIC SPECIFICATIONS**
 - Input Voltage: 5 V (USB power supply)
 - Operating Temperature: 14 °F ~ 104 °F (0°C ~ 40°C)
 - Storage Temperature: -40 °F ~ 140 °F (-40°C ~ 60°C)
 - Weight: 0.093 kg (Without bracket) 0.2 kg (with bracket)
 - Dimensions: 4.65 x 1.46 x 1.21" (118 x 37.2 x 30.8 mm)
 - Part Number: 910-2100-020



Scan this Code,
to learn more

SALES AND INQUIRIES

Headquarters

5225 Wiley Post Way
Suite 500
Salt Lake City, UT 84116

US & Canada

Tel: +1.801.975.7200

International

Tel: +1.801.975.7200

Sales

Tel: +1.801.975.7200
sales@clearone.com

Tech Support

Tel: +1.801.974.3760
videotechsupport@clearone.com