



RG-ES05G/ES08G

5/8-PORT SWITCHES

Product Overview

An Ideal Combination of Quality, Ease of Use & Cost Effectiveness

The Reyee Switch Series consists of 4 models of desktop switches tailored for small enterprises, small-scale surveillance and SOHO. The switches feature plug and play, zero configuration and compatibility with a variety of terminals such as network cameras, printers, PCs, etc., to offer fast deployment experience.

Technical Specifications

Model	RG-ES05G	RG-ES08G
Ports	5x 10/100/1000 Mbps	8x 10/100/1000 Mbps
Operating mode	Half-duplex, full-duplex, auto-negotiation mode Support auto MDI/MDIX	
Backplane bandwidth	16Gbps	
Packet forwarding rate	10Mbps:14880pps 100Mbps:148800pps 1000Mbps:1488000pps	
MAC address	2K	8K
Power supply	External, DC 5.0V / 600mA	External, DC 9.0V / 600mA
Maximum power consumption	≤2.5W	
Fan	Fanless	
Dimensions	108.1mm*64mm*24.8mm	144mm*85mm*23mm
Temperature	Operating temperature: 0 °C ~ 40 °C Storage temperature: -40 °C ~ 70 °C	
Humidity	Operating humidity: 10% ~ 90% RH Storage humidity: 5% ~ 95% RH	